In the claims:

1 1. (Currently Amended) A method comprising:

2 using a data access primitive to model addressability for a memory-mapped device,

3 addressability comprising an address matching function, a lane matching

4 function and one or more bus connections,

5 specifying a first starting address for the memory-mapped device; and

6 [converting] replacing the data access primitive [to] with logic components that

7 implement a first set of addressing matching function, lane matching function

8 and one or more bus connections for the memory-mapped device based upon

9 the data access primitive and the first starting address.

1 2. (Currently Amended) The method of claim 1, further comprising [converting]

2 replacing the data access primitive [to] with logic components that implement a

3 second set of addressing matching function, lane matching function and one or

4 more bus connections for the memory-mapped device based upon the data access

5 primitive and a second starting address.

1 3. (Original) The method of claim 1, further comprising:

2 coupling the data access primitive to the memory-mapped device; and

3 coupling an address bus to the data access primitive.

1 4. (Original) The method of claim 3, wherein the addressing matching function

2 compares an address from the address bus with the first starting address for the

3 memory-mapped device.

1 5. (Original) The method of claim 4, wherein the first starting address is

2 specified by a user.

1 6. (Original) The method of claim 4, wherein the first starting address is

2 generated automatically.

1 7. (Original) The method of claim 6, wherein the first starting address is

2 generated automatically using a set of address constraints.

1 8. (Original) The method of claim 1, wherein the data access primitive is

2 selected to allow addressability for a minimum size transaction supported by the

3 memory-mapped device.

1 9. (Original)The method of claim 8, wherein the memory-mapped device is a register.

1 10. (Currently Amended) A computer readable medium containing executable

2 instructions which, when executed in a processing system, causes the processing

3 system to perform a method comprising:

4 using a data access primitive to model addressability for a memory-mapped device,

5 addressability comprising an address matching function, a lane matching

6 function and one or more bus connections,

7 specifying a first starting address for the memory-mapped device; and

8 [converting] replacing the data access primitive [to] with logic components that

9 implement a first set of addressing matching function, lane matching function

10 and one or more bus connections for the memory-mapped device based upon

11 the data access primitive and the first starting address.

1   11.   (Currently Amended)   The computer readable medium of claim 10, further

2   comprising [converting] <u>replacing</u> the data access primitive logic components that

3   implement a second set of addressing matching function, lane matching function

4   and one or more bus connections for the memory-mapped device based upon the

5   data access primitive and a second starting address.

1   12.   (Original)   The computer readable medium of claim 10, further comprising:

2   coupling the data access primitive to the memory-mapped device; and

3   coupling an address bus to the data access primitive.

1   13.   (Original)   The computer readable medium of claim 12, wherein the

2   addressing matching function compares an address from the address bus with the

3   first starting address for the memory-mapped device.

1   14.   (Original)   The computer readable medium of claim 13, wherein the first

2   starting address is specified by a user.

1   15.   (Original)   The computer readable medium of claim 13, wherein the first

2   starting address is generated automatically.

1   16.   (Original)   The computer readable medium of claim 15, wherein the first

2   starting address is generated automatically using a set of address constraints.

1   17.   (Original)   The computer readable medium of claim 10, wherein the memory-

2   mapped device is selected to allow addressability for a minimum size transaction

3   supported by the memory-mapped device.

1   18.   (Previously Amended)   A method, comprising:

2   selecting a data access primitive to provide data access of a desired transaction

3   size, and to indicate an addressing matching function, a lane matching

4   function and one or more bus connections for a memory-mapped device;

5   specifying an address constraint for the memory-mapped device;

6   instantiating a logic for the memory-mapped device, comprising:

7   generating a starting address for the memory mapped device using the

8   address constraint;

9   using the selected data access primitive and the starting address to map the

10   logic for the memory mapped device capable of being accessed at the

11   desired transaction size, comprising:

12   generating first logic components that implement the address matching

13   function, and

14   generating second logic components that implement the lane matching

15   function and the one or more bus connections.

1   19.   (Original)   The method of claim 18, wherein the address constraint is

2   specified by a user, and wherein the starting address for the memory mapped

3   device is generated automatically.

1   20.   (Original)   The method of claim 18, wherein the transaction size is one in a

2   group comprising a byte, a halfword and a word.

1   21.   (Original)   The method of claim 18, further comprising using a new starting

2   address for the memory-mapped device without having to specify changes to the

3   addressing function, the lane matching function and the one or more bus

4   connections.

1   22.   (Original)   The method of claim 21, wherein different logic for the memory

2   mapped device is instantiated automatically using the same data access primitive

3   and the new starting address.

1   23.   (Unchanged)   The method of claim 18, wherein the addressing matching

2   function compares an address from an address bus coupled with the data access

3   primitive with the starting address, and wherein when there is match, the lane

4   matching function matching the transaction size of a transaction to a respective

5   section of the memory-mapped device.

1   24.   (Previously Amended)   A computer readable medium containing executable

2   instructions which, when executed in a processing system, causes the processing

3   system to perform a method, comprising:

4   selecting a data access primitive to provide data access of a desired transaction

5   size, and to indicate an addressing matching function, a lane matching

6   function and one or more bus connections for a memory-mapped device;

7   specifying an address constraint for the memory-mapped device;

8   instantiating a logic for the memory-mapped device, comprising:

9   generating a starting address for the memory mapped device using the

10   address constraint;

11	using the selected data access primitive and the starting address to map the
12	logic for the memory mapped device capable of being accessed at the
13	desired transaction size, comprising:
14	generating first logic components that implement the address matching
15	function, and
16	generating second logic components that implement the lane matching
17	function and the one or more bus connections.

1   25.   (Original)   The computer readable medium of claim 24, wherein the address

2   constraint is specified by a user, and wherein the starting address for the memory

3   mapped device is generated automatically.

1   26.   (Original)   The computer readable medium of claim 24, wherein the

2   transaction size is one in a group comprising a byte, a halfword and a word.

1   27.   (Original)   The computer readable medium of claim 24, further comprising

2   using a new starting address for the memory mapped device without having to

3   specify changes to the addressing function, the lane matching function and the one

4   or more bus connections.

1   28.   (Previously Amended) The computer readable medium of claim 27, wherein

2   different logic for the memory mapped device is instantiated automatically using

3   the same data access primitive and the new starting address.

1   29.   (Original)   The computer readable medium of claim 24, wherein the

2   addressing matching function compares an address from an address bus coupled

3   with the data access primitive with the starting address, and wherein when there is

match, the lane matching function matching the transaction size of a transaction to ~~a respective section of the memory-mapped device.~~